

CURING & SEALING COMPOUND

- DESCRIPTION
- TYPICAL APPLICATIONS
- FEATURES
- TECHNICAL PROPERTIES
- INSTRUCTION FOR USE

VYKURE P207 is a white pigmented wax emulsion curing compound for new concrete requiring a reflective curing membrane. It maintains adequate moisture in new concrete so that desired properties, such as strength and durability, can develop. This white pigmented formulation also reflects sunlight, helping to keep concrete cool when placed in hot weather.

- Exterior paving
- Walls, columns, and highway barriers
- Residential concrete
- Sidewalks, curbs, and gutters
- Bridge decks and parapet walls
- Commercial concrete

- Forms an efficient moisture barrier for optimum curing of concrete
- Helps ensure proper cement hydration
- Low VOC
- Designed primarily for exterior applications where sunlight reflectivity is needed
- No odor

These technical information was obtained in laboratory tests under normal conditions @ 23°C as following:

FORM	Pigmented wax Emulsion
APPEARANCE	liquid
COLOR	milky white
S.G.	1 kg/lit.
DRYING TIME	1 hrs
RECOAT	3:4 hrs
FOOT TRAFFIC	2:4 hrs

▪ **Surface Preparation**

This product is designed for use on fresh concrete only. The concrete surface should first be finished to the desired texture.

▪ **Mixing**

Agitate before using. Material may separate during long term storage. Mild agitation is recommended before usage.

▪ **Application**

Apply a uniform coverage by spray or roller application. Product may be sprayed with a handheld “pump-up” sprayer or with an airless industrial sprayer. If roller applied, use a short nap sleeve.

▪ **Curing**

For the best cure of freshly placed concrete, apply **VYKURE P207** as soon as possible after finishing operations and/or immediately after the disappearance of the “sheen” of surface moisture.

SPECIFICATIONS

VYKURE P207 ASTM C309, Type 2, Class A. AASHTO M 148, Type 2, Classes A & B

PACKAGING

VYKURE P207 will be packaged in 5.3 gallon (20-liter pails), 56 gallon (210 liter drums) or 266.6 gallon (1000 liter tanks).

COVERAGE

VYKURE P207 will cover 6:8 m² / lit., coverage will vary depending on surface porosity and texture.

SHELF LIFE

VYKURE P207 will be ready for use 12 months if stored in original unopened packs.

STORAGE

VYKURE P207 should be stored in clean ground over plastic or wooden pallets out from direct sun light and moisture at temperature between +5°C to +35°C

CLEAN UP

Clean all tools and application equipment with water immediately after use before the material hardens.

PRECAUTIONS

- **VYKURE P207** should not be applied in hot direct sunlight.
- **VYKURE P207** should not be applied over bleed water.
- **VYKURE P207** should not be applied in rainy weather.
- **VYKURE P207** is nonflammable avoid the direct contact with eye.

CONTACT US:

+201000005513 - +201000005526 - +20224181260

support@vycon-eg.com

www.vycon-eg.com

VYCON CHEMICALS

PIECE 4/1 A3 10TH OF RAMADAN
PIECE 213 NEW INVESTMENT ZONE
A6 10TH OF RAMADAN



Scan me!